- If a cluster command is defined to be invoked as the result of a groupcast, the command SHALL be invoked with an Invoke Request action which SHALL start a new transaction.
- Each path in an Invoke Request or Invoke Response action SHALL indicate a server cluster.

Invoke Request action is either the first action of the Invoke transaction or it follows a successful Timed Request action. See Section 8.2.5, “Common Action Behavior” for behavior common to all actions. The specific action information for this action is shown below.

8.8.2.1. Invoke Request Action Information

Action Field	Type	Constraint	Conformance	Description
SuppressResponse	bool		M	do not send a response to this action
TimedRequest	bool		M	flag action as part of a timed invoke transaction
InvokeRequests	list[CommandDataIB]	desc	M	cluster command(s)

8.8.2.2. Outgoing Invoke Request Action

- This action SHALL be generated as the first action in an Invoke transaction, or following a Timed Request action and successful Status Response action.
- If this action is part of a Timed Invoke transaction, TimedRequest SHALL be TRUE, else FALSE.
- A valid CommandDataIB SHALL be one in the table Valid Command Paths.
- If InvokeRequests has 1 CommandDataIB,
    - the path indicated in that CommandDataIB MAY target a group or a wildcard.
- Else (InvokeRequests has more than 1 CommandDataIB),
    - each path indicated in InvokeRequests SHALL be a concrete (non-wildcard) path and SHALL NOT target a group, and
    - each path indicated in InvokeRequests SHALL be unique.
    - The total number of CommandDataIB in InvokeRequests SHALL NOT exceed what the server indicates it can handle (See MaxPathsPerInvoke Attribute).
    - Care must be taken to avoid issuing a set of commands with some data dependencies between them, since there is no guarantee of "happens-after" in the ordering.

NOTE	For InteractionModelRevision <= 11, having more than one command in InvokeRequests was marked as provisional.

8.8.2.3. Incoming Invoke Request Action

- If this action is part of a Timed Invoke transaction, and the Timeout has expired from the pre-

 Copyright © Connectivity Standards Alliance, Inc. All rights reserved.