liseconds).

- Example: SII=5300 to override the initial retry interval value to 5.3 seconds.

- The optional key SAI indicates the SESSION_ACTIVE_INTERVAL of the Node. This key defines the MRP retry interval for a Node that is Active. This key MAY optionally be provided by a Node to override the default setting. If the key is not included or invalid, the Node querying the service record SHALL use the default MRP parameter value. The SAI value is an unsigned integer with units of milliseconds and SHALL be encoded as a variable-length decimal number in ASCII encoding, omitting any leading zeros. The SAI value SHALL NOT exceed 3600000 (1 hour in milliseconds).
    - Example: SAI=1250 to override the active retry interval value to 1.25 seconds.
- The optional key SAT indicates the SESSION_ACTIVE_THRESHOLD of the Node. This key defines the duration of time the Node stays Active after the last network activity. This key MAY optionally be provided by a Node to override the default setting. If the key is not included or invalid, the Node querying the service record SHALL use the default MRP parameter value. The SAT value is an unsigned integer with units of milliseconds and SHALL be encoded as a variable-length decimal number in ASCII encoding, omitting any leading zeros. The SAT value SHALL NOT exceed 65535 (65.535 seconds).
    - Example: SAT=1250 to override the active retry interval value to 1.25 seconds.

This key defines the duration of time the Node stays Active after the last network activity.

- The optional key T indicates various additional transport protocol modes, apart from MRP over UDP, that are supported by a Node. If the key is not included or invalid, the Node querying the service record SHALL assume the default value of T=0 indicating that only MRP is supported as a transport protocol. The T key, if included, SHALL be encoded as a decimal number in ASCII text, omitting any leading zeroes.
    - It represents a base-10 numeric value for a bitmap of various additional transport protocol modes supported by the advertising Node.
    - For example, the T=6 key/value pair represents a value with bits 1 and 2 set, and bit 0 cleared.
    - Bit index 0 is deprecated and SHALL always be set to 0 by the advertising node and ignored by nodes processing this key.
    - The fields in the bitmap for values of the T key are currently defined in Table 7, "Supported Transport Mode Values".
      Thus, a Node advertising with key T=6 represents both a TCP client and a TCP server, but a Node advertising with T=2 can only be a TCP client.

Table 7. Supported Transport Mode Values

Bit index	Name	Description
0	Reserved	This bit index is deprecated and SHALL be set to 0. Clients SHALL silently ignore this bit.

