

11.26.7. Events	1119
12. Multiple Fabrics	1121
12.1. Introduction	1121
12.2. Joint Fabric	1121
12.2.1. Introduction	1121
12.2.2. Node ID Generation	1121
12.2.3. Anchor ICAC requirements	1121
12.2.4. Joint Fabric ACL Architecture	1122
12.2.5. Joint Commissioning Method (JCM)	1123
12.2.6. Anchor Administrator Selection	1129
12.2.7. Administrator Removal	1131
12.3. User Consent	1131
12.4. Administrator-Assisted Commissioning Method	1131
12.5. Node Behavior	1132
12.6. Fabric Synchronization	1132
12.6.1. Introduction	1132
12.6.2. Terminology	1132
12.6.3. Fabric Synchronization Composition	1133
12.6.4. Preventing Device Duplication	1134
12.6.5. Changes to device and locations of Synchronized Devices	1135
12.6.6. Changes to the set of Synchronized Devices	1136
12.6.7. Fabric Synchronized Relationships	1136
12.6.8. Setup flow for Fabric Synchronization	1137
13. Security Requirements	1143
13.1. Overview	1143
13.2. Device vs. Node	1143
13.3. Commissioning	1143
13.4. Factory Reset	1144
13.5. Firmware	1144
13.6. Security Best Practices	1145
13.6.1. Cryptography	1145
13.6.2. Commissioning and Administration	1145
13.6.3. Firmware	1146
13.6.4. Manufacturing	1146
13.6.5. Resiliency	1146
13.6.6. Battery Powered Devices	1146
13.6.7. Tamper Resistance	1147
13.6.8. Product Security	1147
13.6.9. Bridging	1147
13.6.10. Distributed Compliance Ledger	1147
13.6.11. Safety	1147