

Acronym	Definition
ULA	Unique local address
UTC	Universal Time Coordinated
UUID	Universally Unique Identifier
VID	Vendor Identifier (also Vendor ID)
WPA	Wi-Fi Protected Access
ZCL	Zigbee Cluster Library

1.3. Definitions

Term	Definition
Access Control List	A list of entries in the Access Control Cluster expressing individual rules which grant privileges to access cluster elements.
Administrator	A Node having Administer privilege over at least the Access Control Cluster of another Node.
Advertising Data	A data container used in BLE Advertisements to convey a logical grouping of information.
Anchor CA	This RCAC belongs to Anchor Fabric and is trusted by all devices in the Joint Fabric. It also signs ICA belonging to other fabrics that participate in Joint Fabric. Identical with the TRCA of the Joint Fabric.
Anchor Fabric	This is the fabric that “anchors” Joint Fabric because its operational root CA is trusted by all other fabrics in the Joint Fabric.
Anchor Administrator	Administrator that has the ability to interact with the Anchor CA.
Attribute	A data entity which represents a physical quantity or state. This data is communicated to other Nodes using commands.
Binding	A persistent attachment between an instance on one Node to one-or-more corresponding instances on another (or the same) Node.
Border Router	A router, also known as Edge Router, that provides routing services between two IP subnets (typically, between a hub network and a peripheral network).
Bridge	A Node that represents one or more non-Matter devices on the Fabric.
Bridged Device	A non-Matter device that is represented on the Fabric by a Bridge so it can be used by Nodes on the Fabric.
Broadcast	The transmission of a message to every Node in a particular broadcast domain, be it all Nodes on a Ethernet or Wi-Fi link, and/or all Nodes on a Thread mesh.
Certificate Authority (CA)	An entity that issues digital certificates such as a DAC or NOC