

Table 1. Vendor ID Allocations

Range	Type
0x0000	Matter Standard
0x0001 - 0xFFFF0	reserved for individual Manufacturer Codes as per Connectivity Standards Alliance Manufacturer Code Database
0xFFFF1	Test Vendor #1
0xFFFF2	Test Vendor #2
0xFFFF3	Test Vendor #3
0xFFFF4	Test Vendor #4

All other allocations of Vendor ID are specified in [Connectivity Standards Alliance Manufacturer Code Database](#).

NOTE

The *Test Vendor* IDs are reserved for test and development by device manufacturers or hobbyists. Commissioners SHOULD NOT commission devices using one of these VIDs onto an operational Fabric under normal operation unless the user is made fully aware of the security risks of providing an uncertified device with operational and networking credentials.

2.5.3. Product Identifier (Product ID, PID)

A Product Identifier (Product ID or PID) is a 16-bit number that uniquely identifies a product of a vendor. The Product ID is assigned by the vendor and SHALL be unique for each product within a [Vendor ID](#). Once a Product ID has been used, it SHALL NOT be reused by a different product type under the same Vendor ID. These Product IDs SHOULD NOT be specific to a unique physical device; rather they describe the product type, which might have many manufactured instances (e.g. multiple colors of the same product type).

A value of 0x0000 SHALL NOT be assigned to a product since Product ID = 0x0000 is used for these specific cases:

- To announce an anonymized Product ID as part of device discovery (see [Section 5.4.2, “Announcement by Device”](#)).
- To indicate an [OTA software update file](#) applies to multiple Product IDs equally.
- To avoid confusion when presenting the [Onboarding Payload for ECM with multiple nodes](#).

2.5.4. Group Identifier (GID)

A Group Identifier (Group ID or GID) is a 16-bit number that identifies a set of Nodes across a Fabric at the message layer (see [Section 4.17, “Group Key Management”](#)). A Group ID can further be bound to one or more Endpoints within each Node in the group at the interaction layer.

The Group ID space is allocated as described in [Table 2, “Group ID Allocations”](#):