

Table 2. Group ID Allocations

Range	Type
0xFF00 - 0xFFFF	Universal Group ID range reserved for static multi-cast and anycast identifiers
0x0001 - 0xFEFF	Application Group ID, assigned by fabric Administrator
0x0000	Null or unspecified Group ID

2.5.4.1. Universal Group ID

A Universal Group ID (UGID) is one that resides in the 16-bit subrange of Group ID that is reserved for groups that are common across this standard. These special multicast, groupcast, or anycast destinations are constant and known to all Nodes on any Fabric. The Universal Group ID space is allocated as described in [Table 3, “Universal Group ID Allocations”](#):

Table 3. Universal Group ID Allocations

Range	Type
0xFFFF	All Nodes
0xFFFFE	All non-ICD Nodes
0xFFFFD	<i>Deprecated</i>
0xFF00-0xFFFC	Reserved for future use

Because the keys and [IPv6 multicast prefixes](#) are different across Fabrics, Universal Groups only enable communication within a specific Fabric.

All Nodes Group

This group is used to message all Nodes in a Fabric.

All non-ICD Nodes Group

This group is used to message all power-capable Nodes in a Fabric. [ICD](#) Nodes SHALL NOT subscribe to this group.

2.5.5. Node Identifier

A Node Identifier (Node ID) is a 64-bit number that uniquely identifies an individual Node or a group of Nodes on a Fabric. The Node Identifier space is allocated as described in [Table 4, “Node Identifier Allocations”](#):

Table 4. Node Identifier Allocations

Range	Type
0xFFFF_FFFF_FFFF_xxxx	Group Node ID