

Range	Type
0xFFFF_FFFF_0000_0000 to 0xFFFF_FFF-F_FFFE_FFFF	Reserved for future use
0xFFFF_FFFE_xxxx_xxxx	Temporary Local Node ID
0xFFFF_FFFD_xxxx_xxxx	CASE Authenticated Tag
0xFFFF_FFFC_xxxx_xxxx to 0xFFFF_FF-FC_FFFF_FFFF	Reserved for future use
0xFFFF_FFFB_xxxx_xxxx	PAKE key identifiers
0xFFFF_FFF0_0000_0000 to 0xFFFF_FF-FA_FFFF_FFFF	Reserved for future use
0x0000_0000_0000_0001 to 0xFFFF_FFE-F_FFFF_FFFF	Operational Node ID
0x0000_0000_0000_0000	Unspecified Node ID

Node IDs are used for core messaging, within the internal APIs, within the data model, and to resolve the operational IPv6 addresses of Nodes (see [Section 4.3.2, “Operational Discovery”](#)).

The span of Node IDs from 0xFFFF_FFF0_0000_0000 to 0xFFFF_FFFF_FFFF_FFFF, as well as the value 0x0000_0000_0000_0000 are both reserved for special uses.

2.5.5.1. Operational Node ID

An Operational Node ID is a 64-bit number that uniquely identifies an individual Node on a Fabric. All messages must have an Operational Node ID as the source address. All unicast messages must have an Operational Node ID as the destination address.

While source or destination address MAY be elided from a message, it SHALL remain unambiguously derivable from the [Session ID](#).

2.5.5.2. Group Node ID

A Group Node ID is a 64-bit Node ID that contains a particular [Group ID](#) in the lower half of the Node ID.

2.5.5.3. Temporary Local Node ID

A Temporary Local Node ID is a 64-bit Node ID that contains an implementation-dependent value in its lower 32 bits. This allows implementations to keep track of connections or transport-layer links and similar housekeeping internal usage purposes in contexts where an Operational Node ID is unavailable.

2.5.5.4. PAKE key identifiers

This subrange of Node ID is used to assign an access control subject to a particular PAKE key as specified in [Section 6.6.2.1.1, “PASE and Group Subjects”](#). An example usage would be to create an ACL entry to provide administrative access to any commissioner communicating via a PASE session