

2.11. Stack Limits

2.11.1. System Model Limits

2.11.1.1. Access Control Limits

- A node SHALL guarantee that there are at least four [Access Control Entries](#) available for every fabric supported by the node.

For example: A node that supports 5 fabrics must support at least 20 ACL entries, and if it supports N entries must enforce that any K fabrics together do not use more than $N - 4 \cdot (5 - K)$ entries.

- Device types MAY impose additional constraints on the number of ACL entries that need to be supported.

2.11.1.2. Group Limits

- A node SHALL support at least one group key per fabric for managing the [IPK](#).
- If the node implements one or more device types with support for the Groups cluster, the node SHALL additionally support the maximum number of the required groups as specified by all of these implemented device types, without going below the following mandatory minima:
 - The node SHALL support at least three group keys per fabric.
 - The node SHALL support at least four group table entries per fabric per endpoint having a Groups cluster instance.
 - Each Groups cluster instance SHALL support adding the endpoint to at least four groups.

For example: A node that supports 5 fabrics and has 1 endpoint with a Groups cluster must support at least 20 group table entries. A node that supports 5 fabrics and has 2 endpoints with a Groups cluster must support at least 40 group table entries.

- A node SHALL support one IPv6 multicast group membership for every operational group it supports.
- Support for [Section 11.2.5.4.9, “GroupKeyMulticastPolicy”](#) field in [GroupKeySetStruct](#) is provisional.

2.11.2. Interaction Model Limits

2.11.2.1. Read Interaction Limits

- A server SHALL ensure that every fabric the node is commissioned into can handle a single [Section 8.4, “Read Interaction”](#) from a client on that fabric containing up to 9 paths.
- A server MAY permit [Read Interactions](#) even when there is no accessing fabric, subject to available resources (e.g over PASE).