

```
    salt = [],
    info = [],
    len = 3 * CRYPTO_SYMMETRIC_KEY_LENGTH_BITS
)
```

1. Set **Key1** to the **CRYPTO_SYMMETRIC_KEY_LENGTH_BITS** most significant bits of **Keys**.
2. Set **Key2** to the next **CRYPTO_SYMMETRIC_KEY_LENGTH_BITS** significant bits of **Keys**.
3. Set **Key3** to the **CRYPTO_SYMMETRIC_KEY_LENGTH_BITS** least significant bits of **Keys**.

3.9. Password-Based Key Derivation Function (PBKDF)

Matter specifies the following password-based key derivation function to compute a derived key from a cryptographically weak password.

Function and description
<pre>bit[len] Crypto_PBKDF(byte[] input, byte[] salt, int iterations, int len)</pre> Returns a value of len bits derived from the input using the salt and iterations iterations.
Type and description
<pre>STRUCTURE Crypto_PBKDFParameterSet</pre> Maintains the set of parameters exchanged between a Commissioner and a Commissionee during their pairing.
Mapping (Version 1.0)
<pre>int CRYPTO_PBKDF_ITERATIONS_MIN := 1000 int CRYPTO_PBKDF_ITERATIONS_MAX := 100000</pre> <pre>Crypto_PBKDF(input, salt, iterations, len) := bit[len] PBKDF2(P := input, S := salt, C := iterations, kLen := len)</pre> PBKDF2() SHALL be the HMAC-based PBKDF function with Crypto_HMAC(key := P, message := U[j-1]) as the auxiliary function HMAC as defined in Section 5.3 of NIST 800-132; it returns a bit array of len bits.