

text using capital letters, e.g., `B75AFB458ECD.<domain>`. In the event that a device performs MAC address randomization for privacy, then the target host name SHALL use the privacy-preserving randomized version and the hostname SHALL be updated in the record every time the underlying link-layer address rotates. Note that it is legal to reuse the same hostname on more than one interface, even if the underlying link-layer address does not match the hostname on that interface, since the goal of using a link-layer address is to ensure local uniqueness of the generated hostname. If future link layers are supported by Matter that do not use 48-bit MAC addresses or 64-bit MAC Extended Address identifiers, then a similar rule will be defined for those technologies.

4.3.1.2. Extended Discovery

A Matter Commissionee that advertises Commissionable Node Discovery service records is not necessarily in a state that will allow Commissioning (this state is referred to below as "in Commissioning Mode"). While [Section 5.4.2.3, "Announcement Duration"](#) is limited for some forms of device advertisement, a Matter device MAY advertise Matter Commissionable Node Discovery service records for longer periods, possibly permanently. Advertising Commissionable Node Discovery when not in Commissioning Mode is referred to here as Extended Discovery. Extended Discovery is allowed only for DNS-SD advertisements and not for the other forms of [Device Discovery](#) such as [BLE Commissioning Discovery](#).

To protect customer privacy on public networks, a Matter Commissionee SHALL provide a way for the customer to set a timeout on Extended Discovery, or otherwise disable Extended Discovery. The default behavior for Commissionable Node Discovery SHOULD default to limiting announcement as defined in [Section 5.4.2.3, "Announcement Duration"](#) unless the Manufacturer wishes to enable longer periods for specific use cases.

4.3.1.3. Commissioning Subtypes

The following subtypes for Matter Commissionable Node Discovery are defined:

1. `_L<dddd>`, where `<dddd>` provides the full 12-bit [discriminator](#), encoded as a variable-length decimal number in ASCII text, omitting any leading zeroes.
2. `_S<dd>`, where `<dd>` provides the upper 4 bits of the [discriminator](#), encoded as a variable-length decimal number in ASCII text, omitting any leading zeroes.
3. `_V<dddd>`, where `<dddd>` provides the 16-bit [Vendor ID](#), encoded as a variable-length decimal number in ASCII text, omitting any leading zeroes.
4. `_T<ddd>`, where `<ddd>` provides the [device type](#) identifier for the device, encoded as a variable-length decimal number in ASCII (UTF-8) text, omitting any leading zeroes. In case the device combines multiple device types, the manufacturer SHOULD choose the device type identifier of the primary function of the device for which the device wishes to be discoverable.
5. `_CM`, which represents "currently in Commissioning Mode" (due to any method, for example, a factory new device that has just been put into commissioning mode by the user, or an already-commissioned device which has just received the [OpenCommissioningWindow](#) command).

The *long discriminator* subtype (e.g., `_L840`) enables filtering of results to find only Commissionees that match the full discriminator code, as provided in the [onboarding payload](#).

The *short discriminator* subtype (e.g., `_S3`) enables filtering of results to find only Commissionees