

Note 3: bit 1 (Administrator), bit 2 (Anchor), and bit 3 (Datastore) SHALL all be set for the single device which is the Joint Fabric Datastore.

For example:

- A **JF=1** key/value pair (bit 0 is set) indicates that the Administrator Node is capable of being a Joint Fabric Administrator but has not been commissioned onto the Joint Fabric.
- A **JF=14** key/value pair (bits 1, 2, and 3 are set) indicates that the device is a Joint Fabric Administrator, the Joint Fabric Anchor, and a Joint Fabric Datastore device.
- A **JF=2** key/value pair (bit 1 is set) indicates that the device is a Joint Fabric Administrator but NOT the Joint Fabric Anchor or a Joint Fabric Datastore device.

This value MAY change during the lifecycle of the device.

For example, a device might have a value with bit 0 (Available) set, bit 1 (Administrator) unset, bit 2 (Anchor) unset and bit 3 (Datastore) unset prior to being commissioned onto the Joint Fabric, and then have a value with bit 0 (Available) unset and bit 1 (Administrator) set after it has been commissioned onto the Joint Fabric.

The **VP** key SHALL be present in the DNS-SD TXT record if the **JF** key is present and SHALL provide the Vendor ID of the device.

For example:

VP=123 gives the Vendor ID associated with the Joint Fabric Administrator device.

4.3.1.14. Examples

The examples below simulate a Node in commissioning mode advertising its availability for commissioning.

Examples are shown using both the **dns-sd** command-line test tool and the **avahi** command-line test tool. The **dns-sd** command-line test tool is included in all versions of macOS. It is installed as a DOS command with Bonjour for Windows, and is available on Linux by installing the [mDNSResponder package](https://github.com/balaji-reddy/mDNSResponder) [https://github.com/balaji-reddy/mDNSResponder]. The Avahi package of command line tools is available from the [Avahi project](https://github.com/lathiat/avahi) [https://github.com/lathiat/avahi] for most Linux distributions.

These examples are given for illustrative purposes only. Real Matter Commissionees and Commissioners would not use a command-line test tool for advertising and discovery. Real Matter Commissionees and Commissioners would use the appropriate DNS-SD APIs in their respective chosen programming languages.

Consider a device on Wi-Fi using the 48-bit device MAC address of **B75AFB458ECD** as its host name and a value of **DD200C20D25AE5F7** as its commissionable service instance name. DNS-SD records for it can be set up as follows:

```
dns-sd -R DD200C20D25AE5F7 _matterc._udp,_S3,_L840,_CM . 11111 D=840 CM=2
```

or