

_V123._sub._matterd._udp.local.	PTR	DD200C20D25AE5F7._matterd._udp.local.
_T35._sub._matterd._udp.local.	PTR	DD200C20D25AE5F7._matterd._udp.local.
DD200C20D25AE5F7._matterd._udp.local.	TXT	"VP=123+456" "DT=35" "DN=Living Room TV"
DD200C20D25AE5F7._matterd._udp.local.	SRV	0 0 33333 B75AFB458ECD.local.
B75AFB458ECD.local.	AAAA	fe80::f515:576f:9783:3f30

The port number 33333 is given here purely as an example.

A Commissionee can discover all Commissioners:

```
dns-sd -B _matterd._udp
```

or

```
avahi-browse _matterd._udp -r
```

A Commissionee can discover Commissioners with device type 35:

```
dns-sd -B _matterd._udp,_T35
```

or

```
avahi-browse _T35._sub._matterd._udp -r
```

A Commissionee can discover Commissioners with Vendor ID 123:

```
dns-sd -B _matterd._udp,_V123
```

or

```
avahi-browse _V123._sub._matterd._udp -r
```

4.3.4. Common TXT Key/Value Pairs

The TXT records provided during Commissionable, Operational and Commissioner discovery MAY contain the following optional key/value pairs which are common to every discovery method:

- The optional key **SII** indicates the **SESSION_IDLE_INTERVAL** of the Node. This key defines the **MRP retry interval** for a Node that is Idle. This key MAY optionally be provided by a Node to override the default setting. If the key is not included or invalid, the Node querying the service record SHALL use the default MRP parameter value. The **SII** value is an unsigned integer with units of milliseconds and SHALL be encoded as a variable-length decimal number in ASCII encoding, omitting any leading zeros. The **SII** value SHALL NOT exceed 3600000 (1 hour in mil-