

4.4.1. Message Header Field Descriptions

4.4.1.1. Message Flags (8 bits)

An unsigned integer bit field containing the following subfields:

Table 10. Message Flags field definition

bit 7	6	5	4	3	2	1	0
Version				-	S	DSIZ	

NOTE

All unused bits in the Message Flags field are reserved and SHALL be set to zero on transmission and SHALL be silently ignored on reception.

Version (4 bits, positions 4-7)

An unsigned integer specifying the version of the Matter Message format used to encode the message. Currently only one version is defined:

- 0 — Matter Message Format version 1.0
- 1-15 — Reserved for future use

Messages with version field set to reserved values SHALL be dropped without sending a message-layer acknowledgement.

NOTE

The Version field conveys information solely about the structure of the Matter message itself, not about the structure of the application payload or the interpretation of the message’s type. Thus, changes to how an application handles or interprets a message do not result in the creation of a new message format version number.

S Flag (1 bit, position 2)

A single bit field which SHALL be set if and only if the [Source Node ID](#) field is present.

DSIZ Field (2 bits, position 0-1)

This field SHALL indicate the size and meaning of the [Destination Node ID](#) field.

- 0 — Destination Node ID field is not present
- 1 — Destination Node ID field is present as a 64-bit Node ID
- 2 — Destination Node ID field is present as a 16-bit Group ID
- 3 — Reserved for future use

Messages with DSIZ field set to reserved values SHALL be dropped without sending a message-layer acknowledgement.

4.4.1.2. Session ID (16 bits)

An unsigned integer value identifying the session associated with this message. The session identi-