

3. If the message is a duplicate:
 - a. If the message is marked as encrypted, follow [Section 4.6.5.2, “Use of Message Reception State for Encrypted Messages”](#).
 - b. If the message is marked as unencrypted, follow [Section 4.6.5.3, “Use of Message Reception State for Unencrypted Messages”](#).
 - c. If the message is encrypted and marked as a duplicate, i.e. Message Counter is outside the valid message counter window or marked as previously received in the [Message Reception State](#):
 - i. Perform [Section 4.12.5.2, “Reliable Message Processing of Incoming Messages”](#) on the duplicate message.
 - d. Otherwise, update the Message Reception State as detailed in [Section 4.6.5.1, “Message Reception State”](#), and accept the message for further processing.

4.7. Message Processing

This sub-clause describes the fundamental procedures for transmission and reception.

4.7.1. Message Transmission

To prepare a message for transmission with a given Session ID, Destination Node ID (which may be a [group node id](#) or an [operational node id](#)) and Security Flags, the following steps SHALL be performed, in order:

1. Process the message as described in [Section 4.6.6, “Counter Processing of Outgoing Messages”](#).
2. If the message’s [Session Type](#) is a [Unicast Session](#):
 - a. Set [SessionTimestamp](#) to a timestamp from a clock which would allow for the eventual determination of the last session use relative to other sessions.
 - b. Process the message as described in [Section 4.8.2, “Security Processing of Outgoing Messages”](#).
 - c. Process the message as described in [Section 4.9.3, “Privacy Processing of Outgoing Messages”](#).

4.7.2. Message Reception

To process a received message, the following steps SHALL be performed in order:

1. Perform validity checks on the message; if any fail, processing of the message SHALL stop, and a 'message invalid' error SHOULD be indicated to the next higher layer:
 - a. The [Version](#) field SHALL be [0](#).
 - b. If the message is of [Secure Unicast Session Type](#):
 - i. The [DSIZ](#) field SHALL NOT indicate a Group ID is present.
 - c. If the message is of [Group Session Type](#):
 - i. The [DSIZ](#) field SHALL NOT be [0](#).