

- ii. The **S Flag** field SHALL NOT be **0**.
2. If the message is NOT of **Unsecured Session Type**:
  - a. Obtain the Privacy and Encryption Keys associated with the given Session ID:
    - i. If no keys are found, security processing SHALL indicate a failure to the next higher layer with a status of 'message security failed' and no further security processing SHALL be done on this message.
  - b. For each Privacy and Encryption Key, of which there may be more than one in the case of group messages:
    - i. If the **P Flag** is set, follow [Section 4.9.4, “Privacy Processing of Incoming Messages”](#) to deobfuscate the message.
    - ii. Follow [Section 4.8.3, “Security Processing of Incoming Messages”](#) to decrypt and authenticate the message.
3. Follow [Section 4.6.7, “Counter Processing of Incoming Messages”](#) to enforce replay protection and duplicate detection.
4. If the message transport is UDP, follow [Section 4.12.5.2, “Reliable Message Processing of Incoming Messages”](#) to process message reliability.
5. If the message’s **Session Type** is a **Unicast Session**:
  - a. Set **SessionTimestamp** and **ActiveTimestamp** to a timestamp from a clock which would allow for the eventual determination of the last session use relative to other sessions.
6. The received message is then delivered to [Section 4.10.5, “Exchange Message Processing”](#).

## 4.8. Message Security

The detailed steps involved in security processing of outgoing and incoming Matter messages are described in [Section 4.8.2, “Security Processing of Outgoing Messages”](#) and [Section 4.8.3, “Security Processing of Incoming Messages”](#) respectively. [Section 4.8.1, “Data confidentiality and integrity with data origin authentication parameters”](#) defines how the cryptographic parameters are set for securing Matter messages.

### 4.8.1. Data confidentiality and integrity with data origin authentication parameters

This section specifies the parameters to use the data confidentiality and integrity cryptographic primitive as defined in [Section 3.6, “Data Confidentiality and Integrity”](#).

The parameters in this section SHALL apply for all encrypted messages, i.e. all messages except those of **Unsecured Session Type**.

#### 4.8.1.1. Nonce

The nonce SHALL be formatted as specified in [Table 17, “Nonce”](#).

*Table 17. Nonce*