

Octets: 1	4	8
Security Flags	Message Counter	Source Node ID

The nonce used for the Authenticated Encryption with Additional Data (AEAD) algorithm (see [Section 3.6, “Data Confidentiality and Integrity”](#)) for a given message SHALL be defined as the concatenation of the Security Flags, the Message Counter, and the Source Node ID of that message. The scalar fields in the nonce, namely the Message Counter and the Source Node ID SHALL be encoded in little-endian byte order for the purposes of serialization within the nonce, that is, in the same byte ordering as the segment of the message from which its data originates.

The Source Node ID field used in the nonce SHALL be set to the [Operational Node ID](#) of the node originating security protection of the message:

- If the message is of [Secure Unicast Session Type](#):
 - For a [CASE](#) session, the Nonce Source Node ID SHALL be determined via the [Secure Session Context](#) associated with the Session Identifier.
 - For a [PASE](#) session, the Nonce Source Node ID SHALL be [Unspecified Node ID](#).
- If the message is of [Group Session Type](#):
 - The [S Flag](#) of the message SHALL be [1](#) and the Nonce Source Node ID SHALL be the [Source Node ID](#) of the message.
 - If the [S Flag](#) of the message is [0](#) the message SHALL be dropped.

NOTE

Because PASE negotiates strong one-time keys per session and the [I2RKey](#) and [R2IKey](#) are distinct for each direction of communication, the use of the [Unspecified Node ID](#) as the Nonce Source Node ID remains semantically secure.

4.8.2. Security Processing of Outgoing Messages

The process for encrypting Matter messages is depicted graphically in [Figure 8, “Matter Message Encryption”](#) with color code conventions described in [Figure 9, “Matter Message Encryption Legend”](#).