

associated with the session (see [Section 4.13.3.1, “Secure Session Context”](#)). The Node MAY save state necessary to perform [Session Resumption](#), see [Section 4.14.2.2.1, “Session Resumption State”](#) for more details.

4.11.1.5. Busy

When a receiver receives a request to start a new secure session via a [Sigma1](#) or [PBKDFParamRequest](#) message, the receiver MAY respond with the [BUSY StatusReport](#) when it is unable to fulfill the request. The [BUSY StatusReport](#) SHALL:

1. Set the [R Flag](#) to 0
2. Set the [S Flag](#) to 0
3. Set the [StatusReport ProtocolData](#) to a 16-bit (two byte) little-endian value indicating the minimum time in milliseconds to wait before retrying the original request.
4. Set the [Exchange ID](#) to the *Exchange ID* present in the [Sigma1](#) or [PBKDFParamRequest](#) message which triggered this response.

For example, a responder wishing to indicate they are unable to fulfill the request and that the initiator should wait 500 milliseconds before trying again would send `StatusReport(GeneralCode: BUSY, ProtocolId: SECURE_CHANNEL, ProtocolCode: BUSY, ProtocolData: [0xF4, 0x01])`.

The [BUSY StatusReport](#) SHALL NOT be sent in response to any message except for [Sigma1](#) or [PBKDFParamRequest](#).

An initiator receiving a [BUSY StatusReport](#) from a responder SHALL wait for at least a period of *t* milliseconds before retrying the request where *t* is the value obtained from the [Busy StatusReport ProtocolData](#) field.

If the initiator sends a new session establishment request after receiving a [BUSY StatusReport](#), the request SHALL contain new values for all randomized parameters.

4.11.2. Parameters and Constants

[Table 20, “Glossary of constants”](#) is a glossary of constants used in the secure channel protocol, along with a brief description and the default for each constant.

Table 20. Glossary of constants

Constant Name	Description	Value
MSG_COUNTER_WINDOW_SIZE	Maximum number of previously processed message counters to accept from a given Node and key.	32
MSG_COUNTER_SYNC_REQ_JITTER	Maximum amount of random delay before sending a <i>MsgCounterSyncReq</i> when the synchronization request is triggered by receipt of a multicast message.	500 milliseconds