

12. **Resumption ID**: The ID used when resuming a session between the local and remote peer.
13. **SessionTimestamp**: A timestamp indicating the time at which the last message was sent or received. This timestamp SHALL be initialized with the time the session was created. See [Section 4.11.1.1, “Session Establishment - Out of Resources”](#) for more information.
14. **ActiveTimestamp**: A timestamp indicating the time at which the last message was received. This timestamp SHALL be initialized with the time the session was created.
15. The following Session parameters (see [Table 23, “Glossary of Session parameters”](#)):
 - a. *SESSION_IDLE_INTERVAL*
 - b. *SESSION_ACTIVE_INTERVAL*
 - c. *SESSION_ACTIVE_THRESHOLD*
 - d. **PeerActiveMode**: A boolean that tracks whether the peer node is in Active or Idle mode. **PeerActiveMode** is set as follows:

"PeerActiveMode" = ("now()" - "ActiveTimestamp") < "SESSION_ACTIVE_THRESHOLD"

Note that the **Local Fabric Index** and **Peer Fabric Index** reported in the [NOC Response](#) MAY differ in value, while still referring to the same Fabric, since for a given complete [Fabric Reference](#), the short [Fabric Index](#) allocated during commissioning of the respective Nodes on the same Fabric MAY be different. This possible difference is due to the order in which the Fabric in question was joined in the lifecycle of the respective Nodes. See the section on [AddNOC command behavior](#) for details on Fabric Index allocation behavior over time.

There SHALL also be reservation of storage to support [CASE Authenticated Tag \(CAT\)](#) fields. The **CAT** fields are 32-bit values that MAY have been present in RDN [case-authenticated-tag](#) of the remote peer's operational certificate, during [CASE](#).

The **CAT** fields are used to cache Operational Certificate data so that it can be used by the [ACL processing logic](#) to support [CASE Authenticated Tags](#).

Since these fields MAY be omitted from NOCs, they MAY be marked as absent in the context, such that they are not taken into account when missing. When present, they SHALL be stored. Maximum up to 3 **CAT** fields SHALL be supported.

Their value is unused in [PASE](#) session contexts.

4.14. Session Establishment

4.14.1. Passcode-Authenticated Session Establishment (PASE)

This section describes session establishment using a shared [passcode](#) together with an [augmented Password-Authenticated Key Exchange \(PAKE\)](#), in which only one party knows the passcode beforehand, to generate shared keys. This protocol is only used when commissioning a Node (i.e. the Commissionee).