

Message Name	Payload TLV Encoding
PBKDFParamRequest	pbkdfparamreq-struct
PBKDFParamResponse	pbkdfparamresp-struct
Pake1	pake-1-struct
Pake2	pake-2-struct
Pake3	pake-3-struct
PakeFinished	N/A (encoded via StatusReport)

The other fields of the [Message format](#) are not specific to the PASE messages.

For all TLV-encoded PASE messages, any context-specific tags not listed in the associated TLV schemas SHALL be reserved for future use, and SHALL be silently ignored if seen by a recipient which cannot understand them.

Message Exchange

The [PBKDFParamRequest](#), [PBKDFParamResponse](#), [Pake1](#), [Pake2](#), [Pake3](#), and [PakeFinished](#) of a distinct session establishment are part of the same [message exchange](#). The initiator and responder SHALL NOT send encrypted application data in the newly established session until [PakeFinished](#) is received by the initiator within the unencrypted session used for establishment.

Each message SHALL use [PROTOCOL_ID_SECURE_CHANNEL](#) as [Protocol ID](#) and the corresponding [Protocol Opcode](#) as defined in [Table 18](#), “Secure Channel Protocol Opcodes”.

The flags of the [Exchange Flags](#) of the [Protocol Header](#) are defined as follows per PASE message:

Message	I Flag
PBKDFParamRequest	1
PBKDFParamResponse	0
Pake1	1
Pake2	0
Pake3	1

All PASE messages SHALL be sent reliably. This may be implicit (e.g. TCP) or explicit (e.g. [MRP](#) reliable messaging) in the underlying transport.

The other fields of the [Protocol Header](#) are not specific to the PASE messages.

PBKDFParamRequest

This message serves to request the PBKDF parameters, with a payload that follows this TLV schema:

```
pbkdfparamreq-struct => STRUCTURE [ tag-order ]
{
```