

```

sigma-2-tbsdata => STRUCTURE [ tag-order ]
{
    responderNOC          [1] : OCTET STRING,
    responderICAC         [2, optional] : OCTET STRING,
    responderEphPubKey    [3] : ec-pub-key,
    initiatorEphPubKey    [4] : ec-pub-key,
}

sigma-2-tbdata => STRUCTURE [ tag-order ]
{
    responderNOC [1] : OCTET STRING,
    responderICAC [2, optional] : OCTET STRING,
    signature     [3] : ec-signature,
    resumptionID  [4] : OCTET STRING [ length 16 ],
}

sigma-2-struct => STRUCTURE [ tag-order ]
{
    responderRandom      [1] : OCTET STRING [ length 32 ],
    responderSessionId   [2] : UNSIGNED INTEGER [ range 16-bits ],
    responderEphPubKey   [3] : ec-pub-key,
    encrypted2           [4] : OCTET STRING,
    responderSessionParams [5, optional] : session-parameter-struct
}

```

NOTE

[sigma-2-tbsdata](#) is **NOT** transmitted but is instead signed; the signature will be encrypted and transmitted.

1. The responder SHALL [generate a random resumption ID](#) `ResumptionID = Crypto_DRBG(len = 16 * 8)`.
 - a. The responder SHALL set the [Resumption ID](#) in the [Session Context](#) to the value `ResumptionID`.
2. The responder SHALL use the Node Operational Key Pair `ResponderNOKeyPair`, `responderNOC`, and `responderICAC` (if present) corresponding to the NOC obtained in [Section 4.14.2.3.4, “Validate Sigma1”](#).
3. The responder SHALL [generate an ephemeral key pair](#) `ResponderEphKeyPair = Crypto_GenerateKeyPair()`.
4. The responder SHALL [generate a shared secret](#):

```

SharedSecret = Crypto_ECDH(
    privateKey = ResponderEphKeyPair.privateKey,
    publicKey = Msg1.initiatorEphPubKey,

```