

11. The responder SHALL generate a **session identifier** (**ResponderSessionId**) for subsequent identification of this secured session. The **ResponderSessionId** field SHALL NOT overlap with any other existing PASE or CASE **session identifier** in use by the responder. See [Section 4.13.2.4, “Choosing Secure Unicast Session Identifiers”](#) for more details. The responder SHALL set the **Local Session Identifier** in the **Session Context** to the value **ResponderSessionId**.
12. The responder SHALL use the Fabric IPK configured as described in [Section 4.14.2.6.1, “Identity Protection Key \(IPK\)”](#).
13. Any context-specific tags not listed in the above TLV schemas SHALL be reserved for future use, and SHALL be silently ignored if seen by an initiator which cannot understand them.
14. The responder SHALL send a message with **Secure Channel Protocol ID** and **Sigma2 Protocol Opcode** from [Table 18, “Secure Channel Protocol Opcodes”](#) whose payload is the TLV-encoded **Sigma2 Msg2** with an anonymous tag for the outermost struct.

```
Msg2 =
{
    responderRandom      (1) = Random,
    responderSessionId   (2) = ResponderSessionId,
    responderEphPubKey   (3) = ResponderEphKeyPair.publicKey,
    encrypted2           (4) = TBEData2Encrypted,
    responderSessionParams (5) = session-parameter-struct (optional)
}
```

Validate Sigma2

On receipt of **Msg2**, the initiator SHALL perform the following:

1. The initiator SHALL [generate a shared secret](#):

```
SharedSecret = Crypto_ECDH(
    privateKey = InitiatorEphKeyPair.privateKey,
    publicKey = Msg2.responderEphPubKey,
)
```

2. The initiator SHALL [generate the S2K key](#) using **Msg2.responderRandom** as Responder Random and **Msg2.responderEphPubKey** as Responder Ephemeral Public Key.
3. The initiator SHALL [generate the decrypted data](#):

```
byte TBEData2_A[] = {}
byte TBEData2_Nonce[13] = /* "NCASE_Sigma2N" */
    {0x4e, 0x43, 0x41, 0x53, 0x45, 0x5f, 0x53, 0x69,
     0x67, 0x6d, 0x61, 0x32, 0x4e}

Success, TBEData2 = Crypto_AEAD_DecryptVerify(
```