

```

byte S1RK_Info[] = /* "Sigma1_Resume" */
    {0x53, 0x69, 0x67, 0x6d, 0x61, 0x31, 0x5f,
     0x52, 0x65, 0x73, 0x75, 0x6d, 0x65}

S3K_Info
S1RK = Crypto_KDF(
    inputKey = SharedSecret,
    salt = Sigma1.initiatorRandom || ResumptionID,
    info = S1RK_Info,
    len = CRYPTO_SYMMETRIC_KEY_LENGTH_BITS
)

```

where `||` indicates message concatenation and `ResumptionID` is the identifier for the previous session.

Sigma2 Resumption Key

The Sigma2 resumption key SHALL be [generated](#):

```

byte S2RK_Info[] = /* "Sigma2_Resume" */
    {0x53, 0x69, 0x67, 0x6d, 0x61, 0x32, 0x5f,
     0x52, 0x65, 0x73, 0x75, 0x6d, 0x65}

S2RK = Crypto_KDF(
    inputKey = SharedSecret,
    salt = Sigma1.initiatorRandom || ResumptionID,
    info = S2RK_Info,
    len = CRYPTO_SYMMETRIC_KEY_LENGTH_BITS
)

```

where `||` indicates message concatenation and `ResumptionID` is the new identifier for the this session.

Session Encryption Keys

1. A transcript hash SHALL be [generated](#):

```
TranscriptHash = Crypto_Hash(message = Msg1 || Msg2 || Msg3)
```

2. The session encryption keys SHALL be [generated](#):

```

byte SEKeys_Info[] = /* "SessionKeys" */
    {0x53, 0x65, 0x73, 0x73, 0x69, 0x6f, 0x6e, 0x4b,

```