

bit 0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
Ver[4]				Ver[5]				Ver[6]				Ver[7]			
Requested ATT_MTU															
Client Window Size															

H (Handshake) bit

Set to '1' for connection handshake messages.

M (Management) bit

Set to '1' for connection handshake messages.

Ver[i] (Version) nibbles

Used to negotiate the highest version capability between a Device pair. Supported versions are listed once each, newest first, in descending order. Unused version fields are filled with '0'.

The following values are defined:

- 0 — Unused field
- 4 — BTP as defined by Matter v1.0

Requested ATT_MTU

Requested ATT_MTU is a 16-bit unsigned integer field containing the size of the GATT PDU (ATT_MTU) that can be received by the sender minus the size of the GATT header (3). This value is obtained via the standard ATT MTU exchange procedure (see [Bluetooth® Core Specification 4.2 \(amended\)](#) Vol 3, Part F, Section 3.4.2 "MTU Exchange") and is used to validate that both sides of the BLE connection are using the common minimum value. If BTP is not aware of the negotiated GATT MTU, the value SHALL be set to '23', indicating the minimum ATT_MTU defined by GATT. If the client has no preference, the value may be set to '0'.

NOTE

Each GATT PDU used by the BTP protocol introduces 3 byte header overhead making the maximum BTP Segment Size for the session equal to negotiated ATT_MTU-3.

Client Window Size

Value of the maximum receive window size supported by the client, specified in units of BTP packets where each packet may be up to 244 bytes in length. This maximum was chosen so a single BTP segment can fit into a single 255 byte BLE link layer PDU, including all headers from the link layer, L2CAP, GATT, and BTP.

4.19.3.2. BTP Handshake Response

Table 32. BTP Handshake Response format

bit 0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
Control Flags = 0x65								Management Opcode = 0x6C							