

Constant Name	Description	Default
BTP_CONN_RSP_TIMEOUT	The maximum amount of time after sending a BTP Session Handshake request to wait for a BTP Session Handshake response before closing the connection.	5 seconds
BTP_ACK_TIMEOUT	The maximum amount of time after receipt of a segment before a stand-alone ACK must be sent.	15 seconds
BTP_CONN_IDLE_TIMEOUT	The maximum amount of time no unique data has been sent over a BTP session before the Central Device must close the BTP session.	30 seconds

4.19.6. Bluetooth Requirements

The UUID is provided by Bluetooth SIG, Inc. and may only be used by its members in compliance with all terms and conditions of use issued by the Bluetooth SIG, Inc. For more information, visit <https://www.bluetooth.com/specifications/assigned-numbers/16-bit-uuids-for-sdos>.

Use of the Bluetooth extensions feature of this specification and specifically the MATTER_BLE_SERVICE_UUID is strictly prohibited unless the product is certified by both the Bluetooth SIG and the Connectivity Standards Alliance by a member of good standing of both organizations.

Table 36. SIG UUID assignment

Constant Name	Description	Value
MATTER_BLE_SERVICE_UUID	The UUID for the Matter-over-BLE service as assigned by the Bluetooth SIG.	0xFFFF6

4.20. Public Action Frame Transport Protocol (PAFTP)

The Public Action Frame Transport Protocol (PAFTP) is akin to BTP. PAFTP is used when commissioning over Wi-Fi Public Action Frame while BTP is used when commissioning over Bluetooth.

Just like BTP, PAFTP provides a TCP-like layer of reliable, connection-oriented data transfer of Matter commissioning messages in the Service Specific Info field inside the Service Descriptor Extension Attribute inside [WFA-USD](#) Service Discovery Frame (SDF) Follow-up messages. The PAFTP splits Matter message SDU into multiple PAFTP segments, which are each transmitted via a single [WFA-USD](#) SDF Follow-up message (as shown in [Figure 29, “MATTERoPAF: Matter Message / PAFTP layering”](#)). Each [WFA-USD](#) SDF Follow-up message is transmitted via a single Wi-Fi Public Action Frame.

Matter uses PAFTP to define a Matter-over-PAF (MATTERoPAF) Interface. A MATTERoPAF Interface