

H (Handshake) bit

Set to '1' for connection handshake messages.

M (Management) bit

Set to '1' for connection handshake messages.

Ver[i] (Version) nibbles

Used to negotiate the highest version capability between a Device pair. Supported versions are listed once each, newest first, in descending order. Unused version fields are filled with '0'.

The following values are defined:

- 0 — Unused field
- 4 — PAFTP as defined by Matter v1.5

Supported Maximum Service Specific Info Length

Supported Maximum Service Specific Info Length is a 16-bit unsigned integer field containing the maximum size of the service information that can be transmitted and received by the sender in Service Specific Info field in Service Descriptor Extension attribute in [WFA-USD](#) SDF Follow-up message. The PAFTP can query [WFA-USD](#) layer locally within a Device to determine Supported Maximum Service Specific Info Length. If PAFTP is not aware of the Supported Maximum Service Specific Info Length, the value SHALL be set to '350'.

Commissioner Window Size

Value of the maximum receive window size supported by the Commissioner, specified in units of PAFTP packets where each packet length may be up to Supported Maximum Service Specific Info Length bytes minus PAFTP header. This maximum was chosen so a single PAFTP segment can fit into a single [WFA-USD](#) SDF Follow-up message PDU.

4.20.3.2. PAFTP Handshake Response

Table 41. PAFTP Handshake Response format

bit 0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
Control Flags = 0x65								Management Opcode = 0x6C							
Final Protocol Version				Reserved				Selected Maximum Service Specific Info Length (low byte)...							
...Selected Maximum Service Specific Info Length (high byte)															
								Selected Window Size							

H (Handshake) bit

Set to '1' for session handshake messages.