

Data	SW1	SW2
Version	0x69	0x85

In other error cases, a commissionee MAY answer with another error response as described in [ISO/IEC 7816-4](#).

4.21.4.2. TRANSPORT command

Once commissioning has been successfully initiated with the SELECT command, Matter messages SHALL be exchanged using the proprietary TRANSPORT command. This command is defined by instruction (INS) code 0x20 with parameters P1 and P2 encoding the length of the message to transmit.

Table 47. TRANSPORT Command APDU

CLA	INS	P1	P2	Lc	Data	Le
0x80 (unchained) 0x90 (chained)	0x20	...	...	...	...	...

- The **Lc** single-octet field SHALL encode the length in octets of the payload's **Data** field in compliance with [ISO/IEC 7816-4](#). To optimize underlying ISO-DEP chaining, **Lc** SHOULD be less or equal than $\min(255, FSC-10)$.
- **P1** and **P2** SHALL encode the number of octets of the full message to transmit. It is encoded as a 2-bytes integer with **P1** being the most significant byte. In case the full message fits in a single command, the value is equal to **Lc**. In case the message requires chaining, the value is bigger than **Lc**. The same value SHALL be used in all chained commands.
- The **Data** field SHALL contain a fragment of the message to transmit, possibly the only one.
- The **Le** single-octet field SHALL encode the maximum length in octets that the reader/writer can receive in the response APDU in compliance with [ISO/IEC 7816-4](#). To optimize underlying ISO-DEP chaining, **Le** SHOULD encode the value equal to $\min(256, FSD-6)$.

The response APDU allows the responder to transmit a message to the initiator. In case the full message fits within the number of bytes encoded by **Le** in C-APDU, a successful response SHALL be indicated by the **SW1** and **SW2** values in [Table 48](#).

Table 48. TRANSPORT successful Response APDU - Complete

Data	SW1	SW2
Message or last fragment of message to transmit	0x90	0x00

In case the full message does not fit within the number of bytes encoded by **Le** in C-APDU, a successful but incomplete response SHALL be indicated by the **SW1** value in [Table 49](#), and **SW2** SHALL encode the number of bytes of message to be sent in the next **GET RESPONSE** R-APDU.

Table 49. TRANSPORT successful Response APDU - Incomplete message

Data	SW1	SW2
Fragment of message to transmit	0x61	...