

Digit	Contents	Encoding	Notes
16..20	- Product ID	DIGIT[16..20] := (PRODUCT_ID)	Yields a 5-digit decimal number from 00000 to 65535 (0xFFFF/16 bits)
21	- Check Digit	DIGIT[21] := (CHECK_DIGIT)	See Section 5.1.4.1.5, “Check Digit” for encoding

Check Digit

The *CHECK_DIGIT* element is a single decimal digit computed across all of the preceding digits of the Pairing Code using the [Verhoeff](#) algorithm.

5.1.4.2. Copying between applications

When the Manual Pairing Code is presented in an application within a multi-function device, such as an application on a smartphone, it SHOULD provide a mechanism such as a copy button to allow easy conveyance of the information to other commissioners on the same device.

When a Commissioner is implemented as an application within a multi-function device, such as an application on a smartphone, it SHOULD provide a mechanism such as a paste button to allow easy conveyance of the information from an administrator on the same device.

The receiving application SHALL be robust against characters like dashes and spaces that may be included in the string, such as those added for readability by the user, when passed between the applications. For example, a receiving application seeing the code "1234-567-8910" would need to interpret it as "12345678910".

5.1.5. TLV Content

A variable-length [TLV Data](#) section MAY be encoded into the Packed Binary Data Structure. The TLV section MAY consist of manufacturer-specific information elements and/or elements common to Matter, encoded using TLV. All elements SHALL be housed within an anonymous top-level structure container.

5.1.5.1. Manufacturer-specific Elements

Manufacturer-specific elements SHALL be tagged with context-specific tags that have semantics which are defined by the vendor for use in the products using their Vendor ID, and SHALL use tag numbers 0x80 to 0xFF.

Tag numbers 0x00 to 0x7F are reserved to indicate Matter-common elements.

Manufacturer-specific elements inherit the context of the Vendor ID and Product ID provided in the Packed Binary Data Structure described above. All elements SHALL follow the constraints outlined in [Appendix A, Tag-length-value \(TLV\) Encoding Format](#).

5.1.5.2. Matter-common Elements

All elements common to Matter SHALL use tag numbers in the range 0x00 to 0x7F, as defined in the following section.