

cally isolated from the location where the [PAKE](#) verifier is stored and SHALL NOT be accessible to the executing unit handling the [PAKE](#) verifier.

5.1.7.1. Invalid Passcodes

The following Passcodes SHALL NOT be used for the [PASE](#) protocol due to their trivial, insecure nature:

- 00000000
- 11111111
- 22222222
- 33333333
- 44444444
- 55555555
- 66666666
- 77777777
- 88888888
- 99999999
- 12345678
- 87654321

5.1.8. NFC Tag

A Commissioner MAY use, in addition to the [QR Code Format](#) and [Manual Pairing Code](#) as described above, an NFC tag associated with a Commissionee to retrieve the Onboarding Payload. When an NFC tag is used the following requirements are applicable.

- The data contained in the NFC tag SHALL be the same as specified in [QR Code Format](#).
- The NFC tag SHALL be one of the types as defined by [NFC Forum Devices Requirements](#).
- The NFC tag SHALL use the NFC Data Exchange Format (NDEF) as defined by [NFC NDEF 1.0](#).
- The NFC tag SHALL use NDEF messages as defined by [NFC RTD 1.0](#).
- The Onboarding Payload for the NFC tag SHALL use NDEF URI Record Type Definition as defined by [NFC RTD URI 1.0](#) and as specified in the following table.

Table 64. NFC NDEF Representation

Offset	Content	Description
0	0xD1	TNF=0x01, SR=1, MB=1, ME=1
1	0x01	Length of Record Type
2	URI payload size in bytes	Length of payload
3	0x55	Record Name ("U")