

defined below:

Table 66. UDC Messages

Message Name	Payload TLV Encoding
IdentificationDeclaration	IdentificationDeclaration-struct
CommissionerDeclaration	CommissionerDeclaration-struct

The other fields of the [Message format](#) are not specific to the UDC messages.

5.3.4. Message Exchanges

The flags of the [Exchange Flags](#) of the [Protocol Header](#) are defined as follows per UDC message:

Message	I Flag
IdentificationDeclaration	1
CommissionerDeclaration	1

All UDC IdentificationDeclaration messages SHALL be sent without acknowledgement (e.g., unreliably) using UDP, to an IP address found in a A or AAAA record associated with the Commissioner Discovery ([_matterd._udp](#)) service, using UDP with a destination port as found in the [_matterd._udp](#) SRV record.

All UDC CommissionerDeclaration messages SHALL be sent without acknowledgement (e.g., unreliably) using UDP, to the source IP address of the sender of IdentificationDeclaration message, and the port specified in the IdentificationDeclaration message payload.

The Initiator MAY send up to 4 retries. Each retransmission SHALL be delayed by at least 100 ms from the previous transmission.

The other fields of the [Protocol Header](#) are not specific to the UDC messages.

5.3.5. IdentificationDeclaration Message

This message serves to identify the Commissionee. It can also specify information relating to the requested commissioning session, such as whether to display a Passcode entry dialog. It is sent by the Commissionee to the Commissioner.

In addition to a mandatory [instanceName](#) field, which can be used by the Commissioner to perform [Commissionable Node Discovery](#) in order to determine the service IP and Port used to establish a PASE session with the Commissionee, there are a number of optional fields in the IdentificationDeclaration which can be used by the Commissionee to improve performance and usability of the user experience.

The payload for the IdentificationDeclaration message begins with 17 bytes which consist of the DNS-SD instance name defined in [Commissionable Node Discovery](#) encoded as 16 characters of ascii text, followed by a null termination character.

Following the 17 bytes is the encoded IdentificationDeclaration-struct TLV.