

```

instanceName          : OCTET STRING [ length 17 ]
IdentificationDeclaration-struct => STRUCTURE [ tag-order ]
{
    VendorId           [1, optional] : UNSIGNED INTEGER [ range 16-bits ],
    ProductId          [2, optional] : UNSIGNED INTEGER [ range 16-bits ],
    DeviceName         [3, optional] : STRING [ length 0..32 ],
    DeviceType         [4, optional] : UNSIGNED INTEGER [ range 32-bits ],
    PairingInstruction [5, optional] : STRING [ length 0..32 ],
    PairingHint        [6, optional] : UNSIGNED INTEGER [ range 32-bits ],
    RotatingDeviceId   [7, optional] : STRING [ length 0..100 ],
    Port               [8, optional] : UNSIGNED INTEGER [ range 16-bits ],
    TargetAppList      [9, optional] : ARRAY OF
    {
        TargetApp      [10, optional] : STRUCTURE [ tag-order ]
        {
            AppVendorId [11, optional] : UNSIGNED INTEGER [ range 16-bits ],
            AppProductId [12, optional] : UNSIGNED INTEGER [ range 16-bits ],
        },
    },
    NoPasscode         [13, optional] : BOOLEAN,
    CdUponPasscodeDialog [14, optional] : BOOLEAN,
    CommissionerPasscode [15, optional] : BOOLEAN,
    CommissionerPasscodeReady [16, optional] : BOOLEAN,
    CancelPasscode     [17, optional] : BOOLEAN,
    PasscodeLength     [18, optional] : UNSIGNED INTEGER [ range 8-bits ]
}

```

5.3.5.1. Features

5.3.5.1.1. Bypass Commissionable Node Discovery

In practice, the Commissionable Node Discovery step performed by the Commissioner in response to receiving an IdentificationDeclaration can incur 1 second or more of latency. A Commissionee can provide the same information that a Commissioner would obtain through Commissionable Node Discovery by providing this data in the IdentificationDeclaration message.

The Commissioner MAY bypass the Commissionable Node Discovery step of the [Commissioner Discovery from an Existing Device](#) process when it receives the information it needs in the IdentificationDeclaration message, namely, the **Port** field. The Commissionee MAY also include **VendorId**, **ProductId**, **DeviceName**, **DeviceType**, **PairingInstruction**, **PairingHint**, and **RotatingDeviceId** fields in the IdentificationDeclaration message, similar to the existence of these fields in the DNS-SD Commissionable Node Discovery response.

See [Section 5.3.7.2, “UDC with Commissionable Node Discovery bypass”](#).