

Parameter Name	Feature	Description
Passcode-Length	Coordinate Passcode Dialogs	The length of the displayed passcode to inform the Commissioner of the number of digits to request from user.

To send a IdentificationDeclaration message, the Commissionee SHALL:

1. Construct the **instanceName** based upon the DNS-SD instance name defined in [Commissionable Node Discovery](#).
2. To optionally allow the Commissioner to bypass the Commissionable Node Discovery request:
 - a. Construct the **Port** from the service port for PASE as found in the SRV record of the DNS-SD [Commissionable Node Discovery](#) response.
 - b. Optionally, construct the **VendorId** value as described as input to the [TXT key for Vendor ID and Product ID](#).
 - c. Optionally, construct the **ProductId** value as described as input to the [TXT key for Vendor ID and Product ID](#).
 - d. Optionally, construct the **DeviceName** value as described in [TXT key for device name](#).
 - e. Optionally, construct the **DeviceType** value as described in [TXT key for device type](#).
 - f. Optionally, construct the **PairingInstruction** value as described in [TXT key for pairing instruction](#).
 - g. Optionally, construct the **PairingHint** value as described in [TXT key for pairing hint](#).
 - h. Optionally, construct the **RotatingDeviceId** value as described in [TXT key for rotating device identifier](#).
3. Optionally, construct the **TargetApplList** based upon the set of content app vid/pids that can be used for authentication. This is a subset of vid/pid selected by the Commissioner based upon the vid/pid of the client.
4. To optionally prevent the Commissioner from automatically showing a Passcode dialog:
 - a. Construct **NoPasscode** and set to true to indicate that this message SHOULD only trigger a commissioning session if it can be done without asking the user to input a Passcode (e.g. the Passcode was provided by external means). When this field is set to true in the IdentificationDeclaration message, the Commissioner SHALL NOT show a Passcode dialog to the user. Instead, the Commissioner SHOULD send a CommissionerDeclaration message with the NeedsPasscodeDialog field set to true (and potentially NoAppsFound to indicate the reason). The Commissionee can then choose whether to prompt a Passcode dialog (by re-sending the IdentificationDeclaration message without this field) or to abandon this commissioning attempt.
5. To optionally request that the Commissioner send a CommissionerDeclaration message to serve as an indication that the Commissioner has presented a Passcode dialog to the user:
 - a. Construct the **CdUponPasscodeDialog** and set to true. When this field is set to true in the IdentificationDeclaration message, the Commissioner SHOULD send a CommissionerDeclaration message with the **PasscodeDialogDisplayed** set to true upon showing the Passcode input dia-