

2. If Port not provided, then Commissioner reads instanceName, performs Commissionable Node Discovery to determine vid, pid, rotating ID, Device name, PASE IP, PASE Port
3. Commissioner prompts user for permission to commission Device name
4. User approves
5. Commissioner checks for apps granting access to the vid of the Commissionee, applies a filter on this list if the VidList in the IdentificationDeclaration is populated, and attempts to use Account Login on any resulting apps in order to obtain Passcode using rotatingID
6. No app is found
7. Commissioner sends CommissionerDeclaration with the NoAppsFound and NeedsPasscode fields set to true
8. Commissionee informs user that given Commissioner does not support its app. Provides additional instructions as needed.

5.3.7.4.2. UDC with mismatched account

1. UDC with IdentificationDeclaration sent to Commissioner containing NoPasscode set to true
2. If Port not provided, then Commissioner reads instanceName, performs Commissionable Node Discovery to determine vid, pid, rotating ID, Device name, PASE IP, PASE Port
3. Commissioner prompts user for permission to commission Device name
4. User approves
5. Commissioner checks for apps granting access to the vid of the Commissionee, applies a filter on this list if the VidList in the IdentificationDeclaration is populated, and attempts to use Account Login on any resulting apps in order to obtain Passcode using rotatingID
6. App is found but does not return Passcode
7. Commissioner sends CommissionerDeclaration with the NeedsPasscode field set to true
8. Commissionee informs user that its app has a different active account. Provides additional instructions as needed.

5.3.7.5. UDC with Commissioner-generated Passcode

This allows the Commissionee to utilize a Passcode code generated and displayed on the Commissioner, and input by the user into the Commissionee, rather than the Regular UDC flow where the Passcode code is generated and displayed on the Commissionee, and input by the user into the Commissioner. This flow can simplify the user experience when the Commissionee is a mobile phone app and the Commissioner is a TV since it can be easier to enter a Passcode on a mobile phone than a TV.

1. Commissionee performs Commissioner Discovery, prompts user to select a Commissioner.
2. Selected Commissioner indicates support for [Commissioner Passcode feature](#) (CP=1) in its DNS-SD TXT record.
3. UDC with IdentificationDeclaration sent to Commissioner containing CommissionerPasscode set to true
4. If Port not provided, then Commissioner reads instanceName, performs Commissionable Node