

5.4.2.4. Discovery Information

This section details the information advertised by a commissionable Node.

Field	Length	Is Required?
Discriminator	12-bit	Yes
Vendor ID	16-bit	No
Product ID	16-bit	No
Extended Data	Variable	No

5.4.2.4.1. Discriminator

A 12-bit value matching the field of the same name in the Onboarding Payload.

5.4.2.4.2. Vendor ID

A 16-bit value identifying the device manufacturer (see [Section 2.5.2, “Vendor Identifier \(Vendor ID, VID\)”](#)).

5.4.2.4.3. Product ID

A 16-bit value identifying the product (see [Section 2.5.3, “Product Identifier \(Product ID, PID\)”](#)).

5.4.2.4.4. Extended Data

Extended Data MAY be made available by commissionable Nodes. This data SHALL be encoded using a standard TLV encoding defined in this section. The location of this data varies based on the Node’s commissioning networking technology.

This extended data SHALL be encoded as a [TLV structure](#) tagged with an anonymous tag.

The members of this structure SHALL use [context-specific tags](#) with the values and meanings shown in the table below.

Tag	Value	Member type	Member Description
RotatingIdTag	0x00	octet string	Rotating Device Identifier

5.4.2.4.4.1. Rotating Device Identifier

Some device makers need a way to uniquely identify a device before it has been commissioned for vendor-specific customer support purposes. For example, the device maker may need this to identify factory software version and related features, manufacturing date, or to assist in recovery when the Onboarding Material has been lost or damaged. In order to avoid privacy issues associated with exposing a fixed unique identifier, devices MAY utilize a Rotating Device Identifier for identification purposes. A Rotating Device Identifier is similar to a serial number but rotates at pre-defined moments.

The Rotating Device Identifier provides a non-trackable identifier which is unique per-device and that can be used in one or more of the following ways: