

5.4.2.5.3. Interval

Commissionable devices SHOULD use an Advertising Interval between 20 ms and 60 ms for the first 30 seconds and a value between 150 ms to 1285 ms for the rest of the Announcement duration. Shorter intervals typically result in shorter discovery times.

If a device opts to use [Extended Announcement](#), it SHALL switch to using an Advertising Interval larger or equal to 1200 ms and SHOULD use a nominal Advertising Interval of 1285 ms. When using Extended Announcement, the device SHALL set the Extended Announcement Flag in the Matter Service Data in the BLE Advertisement (see [Table 70, “Matter BLE Service Data payload format — Commissionable OpCode”](#)).

5.4.2.5.4. Advertising Mode

Commissionable devices SHALL use the GAP General Discoverable mode, sending connectable undirected advertising events.

5.4.2.5.5. Advertising Address

To ensure privacy, commissionable devices SHALL use LE Random Device Address (see [Bluetooth® Core Specification 4.2 \(amended\)](#) Vol 6, Part B, Section 1.3.2.1 "Static device address") for BLE Advertising and SHALL change it at least on every boot.

5.4.2.5.6. Advertising Data

In order to reduce 2.4 GHz spectrum congestion due to active BLE scanning, and to extend battery life in battery-powered devices, all critical data used for device discovery is contained in the Advertising Data rather than the Scan Response Data. This allows a BLE Commissioner to passively scan (i.e., not issue Scan Requests upon receiving scannable advertisements) and still be able to receive all information needed to commission a device.

Note that if additional vendor-specific information is to be conveyed and does not fit within the Advertising Data, it may be included in the Scan Response Data. See [Section 5.4.2.8, “Manufacturer-specific data”](#) for details on including vendor-specific information.

Advertising data for Matter discovery uses "Service Data - 16 bit UUID" advertisement data type (see [Bluetooth® Core Specification Supplement 12](#) Section 1.11 "Service Data"), with 16-bit UUID value of **0xFFF6** (see [Table 36, “SIG UUID assignment”](#)).

All multi-byte values are encoded in little-endian byte order within the service data payload.

The advertising format depends on the value of the Matter BLE Device OpCode. The Device OpCode is always embedded in the first byte of the service data. The following Device OpCode values are defined:

Table 69. Matter BLE Device Opcodes

Value	Description
0x00	Commissionable
0x01	Network Recovery