

ditions. Encoding of the file SHALL be UTF-8.

5.7.4.7.1. **schemaVersion** Field

This field SHALL indicate the version of the JSON schema format. This helps in managing changes to the structure of the schema over time. Whenever there is a change to the schema (such as adding, removing, or modifying fields), the **schemaVersion** SHALL be incremented. This ensures that the software processing these configuration files can recognize which version of the schema it is dealing with and handle it appropriately.

This field SHALL be present in the ESF file.

5.7.4.7.2. **esfRevision** Field

This field is a 16-bit integer version number of the file that SHALL match the Version at [Section 11.23.6.23, “EnhancedSetupFlowTCRevision”](#).

This field SHALL be present in the ESF file.

5.7.4.7.3. **defaultCountry** Field

This field is an ISO 3166-1 alpha-2 country code string that indicates the default country to be used if the user's country is not defined in the file.

This field SHALL be present in the ESF file.

5.7.4.7.4. **countryEntries** Field

This field contains a list of terms and condition entries using the associated country as the key.

This field SHALL be present in the ESF file and contain at least one entry.

5.7.4.7.5. **defaultLanguage** Field

This field is an ISO 639-1 language code string that indicates the default language to be used if the user's language is not defined for a given country.

This field SHALL be present in the ESF file for each entry in countryEntries.

5.7.4.7.6. **languageEntries** Field

This field contains a list of the different texts to be displayed using the associated language as the key.

This field SHALL be present in the ESF file for each entry in countryEntries and contain at least one entry.

5.7.4.7.7. **ordinal** Field

This field SHALL specify which bit number this text maps to in [Section 11.10.6.8, “TCAcknowledgements”](#). Each bit in the map SHALL keep the same purpose through the life of the product to ensure a correct interpretation of a user's response across device firmware versions.