

TLV Tag	Matter name	Length (octets)	String length	ASN.1 OID	Types Allowed in X.509
N/A	matter-oid-vid	2	4	1.3.6.1.4.1.3724.4.2.1	UTF8String, PrintableString
N/A	matter-oid-pid	2	4	1.3.6.1.4.1.3724.4.2.2	UTF8String, PrintableString

6.1.2. Key Identifier Extension Constraints

Whenever an X.509 certificate contains Authority Key Identifier or Subject Key Identifier extensions, the associated Key Identifier SHALL be of a length of 20 octets, consistent with the length of derivation method (1) described in section 4.2.1.2 of [\[RFC 5280\]](#).

Further constraints related to the exact derivation appear in the following subsections:

- Matter Certificates (NOC, ICAC, RCAC) Subject Key Identifier extension: see [Section 6.5.11.4, “Subject Key Identifier Extension”](#)
- Matter Certificates Authority Key Identifier extension: see [Section 6.5.11.5, “Authority Key Identifier Extension”](#)
- Device Attestation Certificate (DAC) extensions: see [Section 6.2.2.3, “Device Attestation Certificate \(DAC\)”](#)
- Product Attestation Intermediate (PAI) Certificate extensions: see [Section 6.2.2.4, “Product Attestation Intermediate \(PAI\) Certificate”](#)
- Product Attestation Authority (PAA) Certificate extensions: see [Section 6.2.2.5, “Product Attestation Authority \(PAA\) Certificate”](#)

6.1.3. Certificate Sizes

All certificates SHALL NOT be longer than 600 bytes in their uncompressed DER format. This constraint SHALL apply to the entire DAC chain (DAC, PAI, PAA) and NOC chain (NOC, ICAC, RCAC).

Wherever [Matter Operational Certificate Encoding](#) representation is used, all certificates SHALL NOT be longer than 400 bytes in their TLV form. This constraint only applies to the NOC chain (NOC, ICAC, RCAC) since the DAC chain (DAC, PAI, PAA) only appears in DER format.

All certificates used within Matter SHOULD be as short as possible.

6.1.4. Presentation of example certificates

Certificate bodies are presented for exemplary purposes in multiple formats within this chapter. Since the translation of an X.509 certificate from ASN.1 DER format to human-readable text format may lose fidelity, especially with regards to equivalent types (e.g., PrintableString versus IA5String versus UTF8String) or serialization when non-standard OIDs are seen, textual examples SHALL NOT be considered to be normative. Only direct encoding of DER encoding, such as PEM blocks, should be used to further study the examples. In case of unforeseen divergence between an example certificate illustration and the normative rules expressed in prose, the normative prose SHALL