

-- Matter Names

-- The second to last RelativeDistinguishedName object in MatterDACName SEQUENCE SHALL contain an

-- attribute with type equal to matter-oid-vid and the last RelativeDistinguishedName object in the

-- SEQUENCE SHALL contain an attribute with type field set to matter-oid-pid

MatterDACName ::= SEQUENCE OF RelativeDistinguishedName

-- There are two acceptable formats for MatterPA name. The first is identical to MatterDACName,

-- i.e. the second to last RelativeDistinguishedName object in MatterPAName SEQUENCE SHALL contain an

-- attribute with type equal to matter-oid-vid and the last RelativeDistinguishedName object in the

-- SEQUENCE SHALL contain an attribute with type field set to matter-oid-pid. In the second acceptable

-- format, the last element of the MatterPAName SEQUENCE SHALL be an RelativeDistinguishedName with

-- an attribute with type field set to matter-oid-vid

MatterPAName ::= SEQUENCE OF RelativeDistinguishedName

-- Object definitions and references

-- X962 OIDs

id-x962 OBJECT IDENTIFIER ::= { iso(1) member-body(2) us(840) ansi-x962(10045) }

id-x962-ecdsa-with-sha256 OBJECT IDENTIFIER ::= { id-x962 signatures(4) ecdsa-with-SHA2(3) ecdsa-with-SHA256(2) }

id-x962-prime256v1 OBJECT IDENTIFIER ::= { id-x962 curves(3) prime(1) prime256v1(7) }

-- Connectivity Standards Alliance and Matter specific OIDs

csa-root OBJECT IDENTIFIER ::= { iso(1) identified-organization(3) dod(6) internet(1) private(4) enterprise(1) zigbee(37244) }

-- root arc for attestation certificates

matter-att-root OBJECT IDENTIFIER ::= { csa-root 2 }