

Fallback method to encode VendorID and ProductID

The "fallback method" requires exactly 9 characters that are safe to use in both `PrintableString` and `UTF8String` for either VendorID or ProductID encoding. Since these VendorID and ProductID substrings have unambiguous format, they MAY be provided anywhere within a `commonName` value, and therefore separator selection does not need to be considered. Note that the standard [RFC 5280](#) length limitation for `commonName` attribute value is 64 characters in total (see `ub-common-name` in [RFC 5280](#)).

Using the "fallback method" for embedding of VendorID and ProductID in `commonName` in the `subject` field of a [Device Attestation Certificate](#) claiming VendorID 0xFFFF1 and ProductID 0x00B1 can be illustrated with the following valid and invalid examples (without the double quotes):

- "ACME Matter Devel DAC 5CDA9899 Mvid:FFF1 Mpid:00B1": valid and recommended since easily human-readable
- "ACME Matter Devel DAC 5CDA9899 Mpid:00B1 Mvid:FFF1": valid and recommended since easily human-readable
- "Mpid:00B1,ACME Matter Devel DAC 5CDA9899,Mvid:FFF1": valid example showing that order or separators are not considered at all for the overall validity of the embedded fields
- "ACME Matter Devel DAC 5CDA9899 Mvid:FFF1Mpid:00B1": valid, but less readable
- "Mvid:FFF1ACME Matter Devel DAC 5CDAMpid:00B19899": valid, but highly discouraged, since embedding of substrings within other substrings may be confusing to human readers.
- "ACME Matter Devel DAC 5CDA9899 Mvid:FF1 Mpid:00B1": invalid, since substring following `Mvid:` is not exactly 4 uppercase hexadecimal digits
- "ACME Matter Devel DAC 5CDA9899 Mvid:fff1 Mpid:00B1": invalid, since substring following `Mvid:` is not exactly 4 uppercase hexadecimal digits
- "ACME Matter Devel DAC 5CDA9899 Mvid:FFF1 Mpid:B1": invalid, since substring following `Mpid:` is not exactly 4 uppercase hexadecimal digits
- "ACME Matter Devel DAC 5CDA9899 Mpid: Mvid:FFF1": invalid, since the prefix `Mpid:` was found but there is no occurrence of `Mpid:` followed by exactly 4 uppercase hexadecimal digits.

In addition, the following example shows a highly discouraged, though technically valid encoding:

- "Mpid:Mvid:FFF1 Mpid:12cd Matter Test Mpid:FE67": VendorID 0xFFFF1 and ProductID 0xFE67 (leftmost match is the correct match for `Mpid:` prefix).
 - Instances such as this example SHOULD be avoided since they can cause confusion in different implementations, even if the rules are obeyed.

If either the Vendor ID ([1.3.6.1.4.1.37244.2.1](#)) or Product ID ([1.3.6.1.4.1.37244.2.2](#)) Matter-specific OIDs appear in any `RelativeDistinguishedName` in the `subject` or `issuer` fields of a certificate which is part of the Device Attestation Certificate chain path, then that certificate within the chain SHALL NOT have its `commonName`, if present, parsed for the "fallback method", in the rest of the `issuer` or `subject` field where the Matter-specific OIDs appear. In other words, considering a field such as `subject` or `issuer`, the presence of either of these OIDs as the `type` for any `AttributeTypeAndValue` within any `RelativeDistinguishedName` of that field SHALL cause the "fallback method" to be skipped altogether for that field. Otherwise, when the "fallback method" can legally be used, it SHALL only be used