

trators.

The revocation information MAY be partitioned over multiple [Device Attestation PKI Revocation Distribution Points Schema](#) entries, as the provider of such information deems fit. In other words, there may be more than one record to consult to determine revocation status of a given certificate.

If a DAC, PAI or PAA certificate contains the [cRLDistributionPoints](#) (see [RFC 5280](#) section 4.2.1.13) extension, it SHALL be ignored, since the [Device Attestation PKI Revocation Distribution Points Schema](#) in the Distributed Compliance Ledger is the only supported method of determining up-to-date revocation status.

CRL delegation (also known as "indirect CRLs") is supported for both PAI and PAA, allowing certificate authorities to delegate CRL signing to other entities. This provides flexibility in managing revocation lists while maintaining security through proper validation chains and reduces operational overhead for certificate authorities.

6.2.4.1. Conceptual algorithm for revocation set construction

To build the list of revoked entities for a given PAI or PAA certificate authority, the table described in the [Device Attestation PKI Revocation Distribution Points Schema](#) can be used with a conceptual algorithm, which can then be used at time of revocation checks.

To build an oracle of revoked entities, the conceptual algorithm is as follows:

- Inputs:
 - List of all entries in the [Device Attestation PKI Revocation Distribution Points](#) table of the Distributed Compliance Ledger.
- Outputs:
 - For each tuple of ([CertificateAuthorityKeyIdentifier](#), [CertificateAuthorityName](#)), a set of [RevokedEntitySerialNumber](#) and an associated tuple of ([CRLSignerCertificate](#), [CRLSignerDelegator](#)) certificates.
 - [CertificateAuthorityKeyIdentifier](#) is the Subject Key Identifier of a PAA or PAI as an octet string (e.g. ASN.1 [OCTET STRING](#), or protobuf [bytes](#)).
 - [CertificateAuthorityName](#) is the X.500 Name associated with the PAA or PAI whose revocation information is being aggregated, as it appears in the [Issuer](#) field of a certificate it issues.
 - [RevokedEntitySerialNumber](#) is a serial number containing a large integer matchable to an ASN.1 [INTEGER](#) as seen in the [CertificateSerialNumber](#) field of an [RFC 5280](#)-compliant certificate.
 - [CRLSignerCertificate](#) is the certificate present in the [CRLSignerCertificate](#) field from the Device Attestation PKI Revocation Distribution Points table entry processed.
 - [CRLSignerDelegator](#) is the certificate present in the [CRLSignerDelegator](#) field from the Device Attestation PKI Revocation Distribution Points table entry processed, if present.

NOTE

While the algorithm here does not mention the recording of any other metadata per revoked entity to simplify illustration, implementers MAY do so to allow richer diag-