

If the revocation set is available but no updated CRL is available beyond the timestamp in the "nextUpdate" field in the PAI or the PAA CRL, the Commissioner MAY assume that no updated revocation information is being provided by the CA. The Commissioner SHOULD notify the user of the fact that commissioning could succeed for some non-genuine devices, due to lack of access to some of the necessary information.

The revocation set SHOULD at least include the [Device Attestation PKI Revocation Distribution Points Schema](#) of the [Distributed Compliance Ledger](#).

Since there may be multiple formats for revocation information developed over time, the algorithm in this section is purposefully described in generic terms that would allow expansion to future formats.

The following conceptual algorithm is an example of how to determine whether a DAC or PAI certificate is "revoked" or "not revoked":

- Inputs:
 - The **AuthorityKeyIdentifier** extension of the certificate being queried.
 - The **issuer** name field of the certificate being queried.
 - The **serialNumber** field of the certificate being queried.
 - A conceptual **RevocationDataSet** indexed by (**CertificateAuthorityKeyIdentifier**, **CertificateAuthorityName**), yielding a set of **RevokedEntitySerialNumber**, and an associated tuple of (**CRLSignerCertificate**, **CRLSignerDelegator**) values.
 - **CertificateAuthorityKeyIdentifier** is the Subject Key Identifier of a PAA or PAI as an octet string (e.g. ASN.1 **OCTET STRING**, or protobuf **bytes**).
 - **CertificateAuthorityName** is the X.500 Name associated with the PAA or PAI whose revocation information is being looked-up.
 - **RevokedEntitySerialNumber** is a serial number containing as an ASN.1 **INTEGER** as seen in the **CertificateSerialNumber** field of an [RFC 5280](#)-conformant certificate.
 - **CRLSignerCertificate** is the certificate that signed the CRL.
 - **CRLSignerDelegator** if present, is the certificate that signed the **CRLSignerCertificate**.
 - See [Section 6.2.4.1, "Conceptual algorithm for revocation set construction"](#) for a usable method to generate this dataset.
- Outputs:
 - A boolean value **IsRevoked**, where true indicates that the entity is revoked, and false indicates that it is not revoked.
- Algorithm:
 1. Initialize **IsRevoked** to FALSE.
 2. Obtain the correct **RevocationSet** by indexing the **RevocationDataSet** by the **AuthorityKeyIdentifier** and **issuer** of the certificate whose status is being determined.
 3. If no matching **RevocationSet** is found, return immediately.
 4. If a matching **RevocationSet** is found, determined if **serialNumber** is a member of the set.