

tifier (SKI) extension value of its certificate.

Any context-specific tags not listed in the above schema for Certification Elements SHALL be reserved for future use, and SHALL be silently ignored if seen by a Commissioner which cannot understand them.

See [Section 6.2.3, “Device Attestation Procedure”](#) for more details about usage of the Certification Declaration fields.

Certification Declaration CMS ASN.1 Encoding Format

```

CertificationDeclaration ::= SEQUENCE {
    version                INTEGER ( v3(3) ),
    digestAlgorithm         OBJECT IDENTIFIER sha256 (2.16.840.1.101.3.4.2.1),
    encapContentInfo       EncapsulatedContentInfo,
    signerInfo             SignerInfo }

EncapsulatedContentInfo ::= SEQUENCE {
    eContentType           OBJECT IDENTIFIER pkcs7-data (1.2.840.113549.1.7.1),
    eContent               OCTET STRING cd_content }

SignerInfo ::= SEQUENCE {
    version                INTEGER ( v3(3) ),
    subjectKeyIdentifier   OCTET STRING,
    digestAlgorithm         OBJECT IDENTIFIER sha256 (2.16.840.1.101.3.4.2.1),
    signatureAlgorithm     OBJECT IDENTIFIER ecdsa-with-SHA256 (1.2.840.10045.4.3.2),
    signature              OCTET STRING }

```

The Certification Declaration encoding rules:

1. The format SHALL only support CMS **version** v3.
2. The **digestAlgorithm** SHALL use the **sha256** algorithm.
3. The **signatureAlgorithm** SHALL use the **ecdsa-with-SHA256** (ECDSA with SHA256) and **secp256r1** curve, as defined in Section 2.4.2 of [SEC 2](#).
4. The **eContentType** SHALL use the **pkcs7-data** type.
5. The **subjectKeyIdentifier** SHALL contain the subject key identifier (SKI) of a well-known Connectivity Standards Alliance certificate, that was used to generate the **signature**. The format of the key identifiers supported is available as part of the Certification Policy.
6. The **eContent** field SHALL contain the TLV-encoded Certification Elements TLV structure (see [Certification Elements TLV structure](#)).

Note that Certification Declarations SHALL NOT be generated by any Node, but rather, they SHALL be stored and transmitted to a Commissioner by a Commissionee during the conveyance of the [Attestation Information](#) in response to an [Attestation Request command](#).