

[quest Command](#)” for the error generated in that situation.

- c. The candidate Node Operational Key Pair SHALL only be committed to persistent storage upon successful execution of the next [AddNOC Command](#) executed with a Node Operational Certificate whose public key matches the candidate key.
 - d. The Node SHALL create a Certificate Signing Request (CSR) by following the format and procedure in [PKCS #10](#), which includes a signature using the Node Operational Private Key (see [RFC 2986](#) section 4.2).
 - e. The CSR’s subject MAY be any value and the device SHOULD NOT expect the final operational certificate to contain any of the CSR’s subject DN attributes.
3. The Node SHALL generate and return the NOCSR Information (see [Section 11.18.4.9, “NOCSR Information”](#) for encoding) to the Commissioner using the [CSRResponse Command](#). The NOCSR Information includes a signature using the Device Attestation Private Key.

Node Operational CSR Information Validation

1. The Commissioner SHALL validate the Device Attestation Signature ([attestation_signature](#)) field from [CSRResponse Command](#):

```
Success = Crypto_Verify(  
    publicKey = Public key from DAC,  
    message = NOCSR Information TBS (nocsr\_tbs),  
    signature = Device Attestation Signature (attestation\_signature)  
)
```

where the fields are encoded as described in [Section 11.18.4.9, “NOCSR Information”](#).

- The [AttestationChallenge](#) SHALL be obtained from a [CASE session](#), [resumed CASE session](#), or [PASE session](#) depending on the method used to establish the secure session within which device attestation is conducted.
 - The CSR Nonce in [NOCSR Information](#) SHALL match the Commissioner’s CSR Nonce.
2. The inner signature in the PKCS#10 [csr](#) sub-field of the [CSRResponse Command](#)’s [NOCSRElements](#) field SHALL be verified, per the definition of CSR signatures in [PKCS #10](#).