

```

04:12:3b:90:f5:.....
ASN1 OID: prime256v1
NIST CURVE: P-256
Attributes:
Requested Extensions:
Signature Algorithm: ecdsa-with-SHA256
30:46:02:21:00:95:ff:.....

```

6.4.8. Node Operational Certificate Renewal

A [NOC](#) can be renewed by an Administrator (a Node that has Administer privileges on the Node to be updated). The Administrator triggers the process by sending an [CSRRequest Command](#).

6.4.9. Node Operational Certificate Revocation

A Node's access to other Nodes can be revoked by removing the associated Node ID from [Access Control Entry subjects](#) where it appears. This action is taken by an Administrator which has the privilege to update the Access Control Cluster for its Nodes.

6.4.10. Fabric Table Vendor ID Verification Procedure

NOTE

Vendors operating operational CAs need to consider whether they are operationally sharing a root with other vendors. This could cause the potential for that other vendor to associate NOC chains with a different vendor, since validation of chaining is done only against the trust anchor (root).

The [Fabrics attribute](#) of the [Operational Credentials Cluster](#) contains a table of all fabrics on which a node is operating, recorded using [FabricDescriptorStructs](#).

The VendorID field of the Fabric attribute MAY be used to identify which organization among the members of the Connectivity Standards Alliance has created the fabric. This information MAY assist in expressing to end-users which "ecosystem" or manufacturer has control of the node via that fabric.

Since it is critical to avoid claiming that a fabric is operated by an entity that the user trusts when it's not actually the case, there is a requirement to be able to authenticate the statement of association of a fabric to a given Vendor ID.

The Fabric Table Vendor ID Verification Procedure aims to verify the authenticity of a Vendor ID bound to a given [Fabric Reference](#) composed of a root public key and Fabric ID.

The procedure is uniform across fabrics and MAY be used even to validate the Vendor ID association of fabrics other than the accessing fabric executing the procedure. This is especially important when providing information to an end-user or other client about all fabrics to which a device is joined.

The procedure supports all types of operational credentials, whether involving a global operational root of trust (i.e. a large number of fabrics share a same root of trust), or not.