

Matter name	Description
matter-vvs-id	Certifies the identity of a Vendor Verification Signer .

The value of **matter-icac-id**, **matter-rcac-id** and **matter-vvs-id** DN attribute types MAY be any 64-bit identifier desired by the certificate's issuer. Apart from marking what type of certificates are involved, they MAY be used for debugging purposes to determine the specific CA in use, for example if different production tiers or regions are used.

6.5.6.3. Matter DN Encoding Rules

The rules that SHALL be followed for Matter-specific attribute types when encoding the subject DN are:

- For a [Matter Node Operational Certificate \(NOC\)](#):
 - The subject DN SHALL encode exactly one **matter-node-id** attribute.
 - The **matter-node-id** attribute's value SHALL be in the Operational Node ID range (0x0000_0000_0000_0001 to 0xFFFF_FFEF_FFFF_FFFF), see [Table 4, “Node Identifier Allocations”](#).
 - The subject DN SHALL encode exactly one **matter-fabric-id** attribute.
 - The **matter-fabric-id** attribute's value SHALL NOT be 0 (see [Section 2.5.1, “Fabric References and Fabric Identifier”](#)).
 - The subject DN SHALL NOT encode any **matter-icac-id** attribute.
 - The subject DN SHALL NOT encode any **matter-rcac-id** attribute.
 - The subject DN MAY encode at most three **matter-noc-cat** attributes.
 - Each **matter-noc-cat** attribute present, if any, SHALL encode a different [CASE Authenticated Tag identifier](#) (upper 16 bits of value) than is used by other **matter-noc-cat** attributes (CATs).
 - The subject DN SHALL NOT encode any **matter-vvs-id** attribute.
- For a [Matter ICA Certificate \(ICAC\)](#):
 - The subject DN SHALL NOT encode any **matter-node-id** attribute.
 - The subject DN MAY encode at most one **matter-fabric-id** attribute.
 - If present, the **matter-fabric-id** attribute's value SHALL NOT be 0 (see [Section 2.5.1, “Fabric References and Fabric Identifier”](#)).
 - The subject DN SHALL encode exactly one **matter-icac-id** attribute.
 - The subject DN SHALL NOT encode any **matter-rcac-id** attribute.
 - The subject DN SHALL NOT encode any **matter-noc-cat** attribute.
 - The subject DN SHALL NOT encode any **matter-vvs-id** attribute.
- For a [Matter Root CA Certificate \(RCAC\)](#):
 - The subject DN SHALL NOT encode any **matter-node-id** attribute.
 - The subject DN MAY encode at most one **matter-fabric-id** attribute.