

```

matter-fabric-id = 0xFAB000000000001D,
common-name      = "ROOT CA HOME 3"
]]

```

The following is an example of subject DN encoding of a [Vendor Verification Signer certificate](#).

```

subject = [[
  common-name = "Acme Vendor Verification",
  matter-vvs-id = 0xEFFF001199887766
]]

```

6.5.7. Validity

The context-specific tags **not-before** [4] and **not-after** [5] SHALL be used to identify the not-before and not-after fields in the Matter certificate structure, which indicate the period of validity for the certificate. These two fields SHALL be encoded as unsigned integers. The value of these fields SHALL be encoded as a UTC time of type **epoch-s** (Epoch Time in Seconds).

Special value 0, when encoded in the **not-after** field, corresponds to the X.509/[RFC 5280](#) defined special time value 99991231235959Z meaning no well-defined expiration date.

6.5.8. Public Key Algorithm

The context-specific tag **pub-key-algo** [7] SHALL be used to identify the public key algorithm field in the Matter certificate structure.

```

public-key-algorithm => UNSIGNED INTEGER [ range 8-bits ]
{
  ec-pub-key = 1,
}

```

The following values SHALL be defined for **public-key-algorithm**:

Table 88. Public Key Algorithm Object Identifiers

Value	ASN.1 OID
1	iso(1) member-body(2) us(840) ansi-x962(10045) keyType(2) ecPublicKey(1)

6.5.9. EC Curve Identifier

The context-specific tag **ec-curve-id** [8] SHALL be used to identify the elliptic curve field in the Matter certificate structure.

```

elliptic-curve-id => UNSIGNED INTEGER [ range 8-bits ]
{

```