

```
keyAgreement      = 0x0010,
keyCertSign       = 0x0020,
CRLSign           = 0x0040,
encipherOnly      = 0x0080,
decipherOnly      = 0x0100,
}
```

6.5.11.3. Extended Key Usage Extension

The extended key usage extension indicates one or more purposes for which the certified public key may be used, in addition to or in place of the basic purposes indicated in the key usage extension.

When present, the extended key usage extension SHALL be treated as **critical** and it SHALL be marked as **critical** in the corresponding X.509 certificate. The **critical** field SHALL NOT be encoded in the Matter certificate structure.

The context-specific tag number **extended-key-usage** [3] SHALL be used to identify an extended key usage extension entry in the Matter certificate **extensions** list.

The **extended-key-usage** field SHALL be encoded as an array of **key-purpose-id** values, where each **key-purpose-id** value SHALL be encoded as 8-bit unsigned integer:

```
key-purpose-id => UNSIGNED INTEGER [ range 8-bits ]
```

The following values SHALL be defined for **key-purpose-id**:

Table 91. Key Purpose Object Identifiers

Value	ASN.1 OID
1	iso(1), organization(3), dod(6), internet(1), security(5), mechanisms(5), pkix(7), 3, serverAuth(1)
2	iso(1), organization(3), dod(6), internet(1), security(5), mechanisms(5), pkix(7), 3, clientAuth(2)
3	iso(1), organization(3), dod(6), internet(1), security(5), mechanisms(5), pkix(7), 3, codeSigning(3)
4	iso(1), organization(3), dod(6), internet(1), security(5), mechanisms(5), pkix(7), 3, emailProtection(4)
5	iso(1), organization(3), dod(6), internet(1), security(5), mechanisms(5), pkix(7), 3, timeStamping(8)
6	iso(1), organization(3), dod(6), internet(1), security(5), mechanisms(5), pkix(7), 3, OCSPSigning(9)

The **key-purpose-id** values in the **extended-key-usage** array SHALL be encoded in the same order as they appeared in the corresponding X.509 certificate.