

```

Restrictions: [
  0: {
    Type: AttributeAccessForbidden, // access limitation for attribute
    Id: 0x0000                      // attribute 0x0000
  },
  1: {
    Type: CommandForbidden, // command limitation
    Id: NULL                // all commands
  },
  2: {
    Type: EventForbidden, // event limitation
    Id: NULL              // all events
  }
]
}
]
ARL: [] // empty
}

```

Upon allocation of a new FabricIndex during commissioning (see [Section 11.18.6.8, “AddNOC Command”](#)), one or more ARL entries with the new FabricIndex MAY be added to the ARL attribute at the time that the initial ACL entry for the new FabricIndex is added. Until CommissioningComplete command is invoked in the GeneralCommissioning cluster, the CommissioningARL continues to apply.

Example:

```

Access Control Cluster: {
  ACL: [
    0: {
      FabricIndex: 1,
      Privilege: Administer,
      AuthMode: CASE,
      Subjects: [ 0xAAAA_AAAA_AAAA_AAAA ],
      Targets: []
    }
  ],
  Extension: [], // empty (omitted hereafter)
  CommissioningARL: [
    0: {
      Endpoint: 1,           // application endpoint 1
      Cluster: 0x0453,       // application cluster 0x0453
      Restrictions: [

```