

The CommissioningARL and ARL attributes SHALL NOT include limitations that would prevent commissioning (see [Section 9.10.4.2.1, “Managed Device Feature Usage Restrictions”](#)). If a wildcard restriction appears in the ARL that would restrict access in such a case, the wildcard MAY appear but the restriction SHALL NOT take effect.

Superimposing this ARL value upon the example earlier in this section, when an Administrator adds, for example, an Access Control Entry which grants **Operate** privilege for the entire Node, to all CASE-authenticated subjects), this grant MAY be further limited by restrictions imposed by the ARL. In other words, even though the ACL entry grants **Operate** privilege to all data model elements, attempts to read or write attribute 0x0000, or to invoke commands upon Cluster 0x0453 of Endpoint 1 would result in an error of ACCESS_RESTRICTED, since the Access Restriction List is a subsequent overriding of an initial privilege granted.

```
Access Control Cluster: {
  ACL: [
    ...
    1: {
      FabricIndex: 1,
      Privilege: View,
      AuthMode: CASE,
      Subjects: [],
      Targets: []
    }
  ],
  CommissioningARL [ ... ], // (omitted hereafter)
  ARL: [
    0: {
      FabricIndex: 1,
      Endpoint: 1,           // application endpoint 1
      Cluster: 0x0453,       // application cluster 0x0453
      Restrictions: [
        0: {
          Type: AttributeAccessForbidden, // access limitation for attribute
          Id: 0x0000                      // attribute 0x0000
        },
        1: {
          Type: CommandForbidden, // command limitation
          Id: NULL                // all commands
        },
        2: {
          Type: EventForbidden, // event limitation
          Id: NULL              // all events
        }
      ]
    }
  ]
}
```