

}

6.6.6. Conceptual Access Control Privilege Granting Algorithm

This section describes an overall Conceptual Access Control Privilege Granting algorithm. Implementations of this algorithm SHALL have an identical outcome to the output of this conceptual algorithm described below.

The Interaction Model protocol, through its message handling, SHALL determine the privilege level granted per Target, on every instance where a Target is referenced for use.

6.6.6.1. Necessary Data Structures

6.6.6.1.1. Access Control List

The [Access Control List](#) contains several [Access Control Entries](#), previously described in [Section 6.6.2, “Model”](#).

The entry fields are:

- Subjects List ([subject-id\[\]](#) [Subjects](#))
- Targets List ([AccessControlTargetStruct\[\]](#) [Targets](#))
- Authentication Mode value ([AccessControlEntryAuthModeEnum](#) [AuthMode](#))
- Privilege value ([AccessControlEntryPrivilegeEnum](#) [Privilege](#))

6.6.6.1.2. Access Restriction List

The [Access Restriction List](#) contains several [Access Restriction Entries](#), previously described in [Section 6.6.2, “Model”](#).

The entry fields are:

- Endpoint ([endpoint-no](#) [Endpoint](#))
- Cluster ([cluster-id](#) [Cluster](#))
- Restrictions List ([AccessRestrictionStruct\[\]](#) [Restrictions](#))

6.6.6.1.3. Incoming Subject Descriptor (ISD) Structure

Each incoming message has a unique [AuthMode](#), [SubjectDescriptor](#) applicable to it, whose derivation is deterministic based on both incoming message fields and session metadata fields. For example, if a message arrives that matches a given CASE Session ID, then the metadata for that CASE session would be used.

Computation of the ISD is described in [Section 6.6.6.3, “Derivation of ISD from Incoming Message”](#).

The ISD fields are as follows:

- Commissioning Flag ([bool](#) [IsCommissioning](#)), whether the authentication is over a commissioning channel for an ongoing commissioning.