

ID	Name	Type	Constraint	Quality	Access	Fallback	Conformance
44	MaxLevel	uint8	0 to 100	F	R V	100	O

7.3.13. Expressions and Optionality

These rules apply to the conformance tags for a cluster:

- A conformance expression supports conformance tags as operands.
- A conformance tag for a cluster MAY be the name of a cluster feature (see [FeatureMap](#)).
- A conformance tag for a cluster MAY be the name of an element in the Name column of the same table.
- A conformance tag for a cluster MAY be the struct field name of an element, when annotated with the name in the Name column, e.g. "<ElementName>.<FieldName>".
- A conformance tag for a cluster MAY be the name of an attribute in the attribute table, when annotated with a reference to the element.
- A conformance tag for a command field of response commands in a cluster MAY be the name of a command field in the associated request command, when annotated with a reference to the element.
- A conformance tag for a device type definition MAY also include a condition of the node.

The annotations MAY be combined, e.g. "<ReferenceToElement>.<StructFieldName>" to use element conformance of a struct field from a Fixed attribute in another table.

Expressions SHALL represent a dependency with boolean logic using:

- the NOT operator such as "!AA"
- the OR operator such as "AA | BB"
- the AND operator such as "AA & BB"
- the XOR (exclusive or) operator such as "AA ^ BB"
- the equal operator such as "AA==10"
- the not equal operator such as "AA!=10"

Equality operators require that a value can be resolved for the left operand. If the left operand is not supported, the [fallback](#) is the value. "NULL" is a valid value for the equality operator.

Simple dependencies MAY also be defined in conformance. If a Max attribute has a dependency on a Min attribute, then the conformance for Max is "Min". Exclusive logic also applies. For example, if the Absolute attribute is mutually exclusive to the Percentage attribute, and one of the two must be supported, then conformance for Absolute would be "!Percentage", and conformance for Percentage would be "!Absolute".

Unless overridden with parentheses, the order of operations is:

- NOT operator "!"